

DULUX S 11 W/840



Luminous flux

Product description: **DULUX S 11 W/840** Product code: 4050300239507

Shipping carton box (VS) contains 10 Piece (PCE)

Quantity:

You can find this product in the eCatalog: http://catalog.myosram.com?~language=EN&~country=DE&it_p=4050300239507

Applications	
Suitable for indoor	Yes
Categorizations	
SEG number	8330028
Certificates & Standards	
EEI - Energy Label	A
General Description	
Rated lamp mercury content	1.4 mg
Base (standard designation)	G23
Recycling	Yes
Technical - Electrical Data	
Rated lamp efficacy (standard condition)	76 lm/W
Rated lamp efficacy (HF data)	Under clarification by authority and standardization body
Construction wattage	11.8 W
Nominal wattage (packaging)	11 W
Technical - Geometries	
Overall length	234.50 mm
Tube diameter	12 mm
Length with base excl. base pins/connect	214 mm
Length	237.00 mm
Length acc. to IEC standard	215 mm
Construction length	234.50 mm
Technical - Lifespan	
Operation mode LLMF/LSF	50 Hz
Rated lamp life time	10000 h
Nominal lamp life time	10000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.85
Technical - Light Technical Data	
Luminous flux at 25 °C	900 lm
Nominal luminous flux	900 lm
Rated color rendering index Ra	80-89
Rated luminous flux	900 lm
. a.ca .aiiiodo iidx	000 IIII

900 lm

Page 1 of 2



DULUX S 11 W/840

Technical - Light Technical Data				
Light color	840			
Rated color temperature	4000 K			
Color rendering index Ra	8089			
Light color as per EN 12464-1	LUMILUX Cool White			
Rated LLMF at 2,000 h	0.85			
Rated LLMF at 4,000 h	0.78			
Rated LLMF at 6,000 h	0.76			
Rated LLMF at 8,000 h	0.76			
Color rendering group	1B			
Color temperature	4000 K			

Technical - Temperatures	
Rated ambient temp.w.max.luminous flux	25.0 °C

Packaging units							
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume			
4050300010618	Folding carton box contains 1 Piece	36,000 mm x 26,000 mm x 239,000 mm	48,300 g (0,000 g)	0,232 Cubic dec.			
4050300239507	Shipping carton box contains 10 Piece	111,000 mm x 133,000 mm x 219,000 mm	536,000 g (0,000 g)	2,688 Cubic dec.			

Their small dimensions and slim design make OSRAM DULUX S lamps ideal for creative lighting.

- Single-ended plug-in base G23 with integrated starter and RF suppression capacitor
 The colored version is ideal for cost-effective creative illumination and decoration